



CUMMINGS

FRONT LEGS: The front legs shall be maple, 1-3/8" x 1-3/8" and set 90 degrees in both directions to the floor. A 3/32" high x 3/32" deep reveal shall be machined into the leg on all four sides 1-1/2" up from the bottom. The front legs shall be mortised, glued flush to the apron rails. The legs shall be reinforced with corner blocks screwed into the legs and rails. All exposed edges shall be sanded to a 1/16" radius.

BACK POSTS: The back posts shall be edge glued maple, 1-3/8" x 1-3/8", profiled to the desired angles and a 3/32" high x 3/32" deep reveal shall be machined into the leg on all four sides 1-1/2" up from the bottom. The back posts shall be mortised, glued flush to the apron rails. The posts shall be reinforced with corner blocks screwed into the legs and rails. All exposed edges shall be sanded to a 1/16" radius.

STRETCHER ASSEMBLY: The assembly shall be solid maple, consisting of two side stretchers, 1-3/8" square tenoned into the front and back legs and glued flush on the leg. Two cross stretchers, 1-3/8" square, shall be tenoned into the side stretchers, and spaced 3-7/8" apart. The header shall be located 8-1/2" off the floor, and shall be parallel to floor. All exposed edges shall be sanded to a 1/16" radius.

CORNER REINFORCEMENT: A mitered corner block shall be glued and screwed at the corner intersection of seat apron rails, legs and back posts. The corner blocks shall be attached to the adjacent apron rails with #10 flat head wood screws. A 3" long hex lag screw with flat washer shall pass through the corner block and into the inside corner of each leg and back post.

BACK ASSEMBLY: The assembly shall consist of a top rail of solid maple and three back options. The top rail shall be 1" thick x 5-1/8" high profiled to match the back posts, and tenoned and glued flush to the back legs. The back options: fully upholstered back shall be an insert, profiled to match back posts, upholstered on both sides, fitted between the top rail and back posts. Full-slat back shall be an 1-3/8" horizontal member, 1-3/8" from top rail, glued flush to the back posts with three solid maple slats, 1-3/8" wide with 1" between slats, spanning from the top rail to the back apron. Partial-slat back shall be an 1-3/8" horizontal member, 1-3/8" from top rail, glued flush to the back posts with three brushed aluminum slats, 1-3/8" wide with 1" between slats, spanning from the top rail to the horizontal member with the lower portion of the back open.

WORDEN


SEAT: The wood seat shall be edge glued solid maple, 1" thick, saddled 1/2" deep with a 1/4" radius along the front edge. The upholstered seat shall consist of 1/2" thick plywood, fit between the side aprons, covered with 1" thick, fire retardant, polyurethane foam with 2.8 lbs. density and 70 lbs. ILD. Seat is then upholstered with selected cover and the bottom side of seat shall be covered with black Accord fabric, attached by means of #10 oval head wood screws, through the corner blocks.

ARMS: The arm shall be 1-3/8" thick x 1-3/8" wide, and glued flush to the back post. The vertical support shall be 1-3/8" x 1-3/8", mortised and tenoned and glued flush to the arm, glued and screwed flush to the side rail. All exposed edges shall be sanded to a 1/16" radius.

GLIDES: All chairs shall have plastic nail glides.


CUMMINGS ARM CHAIR

CUMMINGS SIDE CHAIR



Wood Slat Back with Upholstered Seat
COM: 7/8 yards

Wood Slat Back with Wood Seat



Wood Slat Back with Upholstered Seat
COM: 7/8 yards

Wood Slat Back with Wood Seat



Aluminium Back with Upholstered Seat
COM: 7/8 yards

Aluminium Back with Wood Seat




Aluminium Back with Upholstered Seat
COM: 7/8 yards

Aluminium Back with Wood Seat



Upholstered Seat and Back
COM: 1-1/3 yards

Height: 32"
Depth: 21-3/4"
Width: 21-3/4"
Seat Depth: 17"
Seat Height: 18-1/2"
Arm Height: 26"



Upholstered Seat and Back
COM: 1-1/3 yards

Height: 32"
Depth: 21-3/4"
Width: 21-3/4"
Seat Depth: 17"
Seat Height: 18-1/2"



199 East 17th Street
Holland, Michigan 49423
800.748.0561
wordencompany.com

© 2019 The Worden Company