



rockerDOT

DIMENSIONS: 20 ½" Dia. x 20 ½"H

FRAME: All framework shall be constructed of 1" & 3/4" thick plywood and ¼" thick structural fiberboard tube. All joints are to be glued and screwed/nailed, as required. The frame shall be weighted on the side opposite the handle to create a visual lean to the finished rocker-Dot when it is in a resting position.

SEAT AND FRAME FOAM: The seat shall be glued to the top plate of the frame and frame foam shall be glued to .050"T chipboard that is stapled to the frame. Foam is made of high density, fire retardant polyurethane. The seat cushion foam is 2 inches thick. The frame foam is ½" inch thick and wraps the entire frame. The frame assembly shall be completely wrapped in non-removable fabric.

UPHOLSTERY: All upholstery shall be a tight, weltless design.

HANDLE: The handle shall be constructed of 75% PVC/25% Polyester "Pro-Tuff" brand material. The handle is 2 ½"W x 6"H when installed and shall be secured by two 40mm Joint Connector Screws with a 17mm diameter head, in a nickel finish. The joint connector screws shall be installed through a 3mm thick decorative Sintra plate, used to cover the bottom of the handle. Color option: Red, Black, Gray with stitching color in light gray/silver.

BASE: The base shall be formed from black, .125"T stock sheet ABS with a deep hair cell texture on the outside only. The base shall be attached to the frame using (08) #10 x 2" black, flat head, Phillips screws.



199 East 17th Street
Holland, Michigan 49423
800.748.0561
wordencompany.com

WORDEN

© 2019 The Worden Company